



Product highlights

- ✓ Effective treatment of all vehicle spaces.
- ✓ Disinfection, pest control or odour control
- ✓ Ultra-fine droplet (6.84 μm at 4 bar (58 PSI))



The fogging system for the treatment of vehicle interiors.

Easy handling and short application time with small application quantity.

The **CF-1 CAR** uses the air pressure of an available compressor and a special nozzle technology. This produces a dry fog and ultra-fine droplet spectrum, for a fast and comprehensive treatment of all vehicle compartments.

Thanks to **CF-1 CAR** the fogging of disinfectant treats surfaces as well as hard-to-reach areas.

CF1 Car helps in protecting against the threat of harmful microbes or other disease vectors and makes interiors of all vehicles safer.

Technical data

CF-1 Car

Air volume:	80 l/min (compressor necessary)
Pressure:	6 bar (max.)
Operating pressure:	2 bar
Application rate:	0.1 - 5 l/h
Active substance container:	250 ml
Nozzle and frame:	Stainless steel

Droplet size D (v,0.5) with water at 1.4 l/h application rate and 80 l/min air flow rate

6,84 µm at 4 bar (58 PSI)

8,73 µm at 3 bar (43 PSI)

11,56 µm at 2 bar (29 PSI)

Our solution for these industries

- Car repair shops
- Taxi companies
- Ambulance and nursing services
- Car rental companies
- Transport companies
- Public transport



IGEBA Gerätebau GmbH
Boschensaege 2
87480 Weitnau-Germany
+49-8375-92 00-0
info@igeba.de



more infos...

<https://igeba.de>